



Laser Video Wall


80" UXGA Laser Lit Rear Access Video Wall

- Rich picture quality with Full HD Resolution for superb image quality
- Ultra High Brightness to give the most vivid colors
- High lumens efficiency for reducing operating costs
- Browser/Server based architecture for quick monitoring



80" UXGA Laser Lit Rear Access Video Wall

Delta's Laser Video wall is a rear projection, Laser based UXGA Video wall that offers environment friendly Laser illumination, ultra high brightness and true cube redundancy. Industry's first ultra-bright Laser based DLP® video wall improves energy savings of up to 33%.



LED Light Source



Laser Light Source

Specifications

Model		DVS-806R AN				
Description		Laser Light Source UXGA Cube				
Individual Cube Size		80" Diagonal				
Image Size		1600 x 1200 mm				
Display Technology		DLP, single chip				
Native Resolution		1600 x 1200 pixels				
Aspect Ratio		4:3				
Screen to Screen Gap		Adjustable up to 0.2 mm				
Light Source		Laser				
Brightness		Typ. 2400 lumens ^{*1}				
Brightness Uniformity		Up to 98% ^{*2}				
Contrast Ratio		Typ. 1800:1				
Colors		16.7 million				
Color Temperature Range		3200K to 9300K, Custom				
Standard Inputs ^{*4}		1x Digital DVI-I, 2x Digital HDMI, 1x Analog D-sub 15pin, 1x Display Port				
Standard Outputs ^{*4}		2x Digital HDMI				
Optional Board	I ^{*3}	Inputs	1x Digital DVI-D, 1x HDMI, 1x Display port, 1x Analog 5BNC (RGBHV or YPbPr), 1x Analog S-video			
	II ^{*3}	Inputs	1x Digital DVI-D, 1x 3G-SDI, 1x Display port 1x Analog 5BNC (RGBHV or YPbPr), 1x Analog S-video			
		Output	1x 3G-SDI			
		III ^{*3}	Inputs	1x Digital DVI-D, 1x HD-baseT, 1x Display port 1x Analog 5BNC (RGBHV or YPbPr), 1x Analog S-video		
Control Options		RS-232 / RS 422, IP, IR				
Screen Brightness	Screen Type	Bright mode	Normal mode	ECO mode	Screen Viewing Angle (1/2 Gain)	
	CSI	400 cd/m ²	300 cd/m ²	200 cd/m ²	H: 36°	V: 34°
	XMD-AG	430 cd/m ²	320 cd/m ²	215 cd/m ²	H: 31°	V: 17°
Light source Average Life		60,000 hours	80,000 hours	100,000 hours		
Power Consumption		320 w	250 w	185 w		
Input Voltage		AC 90-240 V @ 50/60 hz				
Power Supply		Dual Power supply available as an option				
Dimension (W x H x D) & Weight		Dimension : 1600 x 1615 x 962.5mm, Net Weight : 180Kg				
Operating Temperature		5°C ~ 40°C (41°F ~ 104°F)				
Non-Operating Temperature		-20°C - 60°C (-4°F ~ 140°F)				
Operating / Storage Humidity		10% ~ 90%, non-condensing				

Note: *1. Bright mode, *2. Through electronical compensation, *3 Only one of the optional boards can be used with standard input / output board, *4 Change from 2020/3.

※ All specifications are subject to change without prior notice.

Ver:06.2020