

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180809-E176972  
**Report Reference** E176972-20180808  
**Issue Date** 2018-AUGUST-09

**Issued to:** DELTA ELECTRONICS INC  
31-1 SHIEN PAN RD  
KUEI SAN INDUSTRIAL ZONE  
TAOYUAN HSIEN  
333 TAIWAN

**This is to certify that representative samples of** POWER CONVERSION EQUIPMENT  
See Addendum

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 61800-5-1, ADJUSTABLE SPEED ELECTRICAL POWER DRIVE SYSTEMS - PART 5-1: SAFETY REQUIREMENTS - ELECTRICAL, THERMAL AND ENERGY  
CSA C22.2 No. 274, ADJUSTABLE SPEED DRIVES

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations>.



# CERTIFICATE OF COMPLIANCE

<b>Certificate Number</b>	20180809-E176972
<b>Report Reference</b>	E176972-20180808
<b>Issue Date</b>	2018-AUGUST-09

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

AC Motor Drive, VFD-ME300 series,  
VFD followed by 0A8, 1A6, 2A5, or 4A8, followed by ME, followed by 11, followed by A, or E followed by N, or F, followed by N, or S, may be followed by H, A, or blank, and may be followed by alphanumeric suffix.

VFD followed by 0A8, 1A6, 7A5, 2A8, 4A8, or 11A, followed by ME, followed by 21, followed by A, or E followed by N, or F, followed by N, or S, may be followed by H, A, or blank, and may be followed by alphanumeric suffix.

VFD followed by 0A8, 1A6, 7A5, 2A8, 4A8, 11A, 17A, or 25A followed by ME, followed by 23, followed by A, or E followed by N, or F, followed by N, or S, may be followed by H, A, or blank, and may be followed by alphanumeric suffix.

VFD, followed by 4A2, 1A5, 2A7, 5A5, 9A0, 13A, 17A, or 25A followed by ME, followed by 43, followed by A, or E followed by N, or F, followed by N, or S, may be followed by H, A, or blank, and may be followed by alphanumeric suffix.

#### Accessories –

Enclosed Type 1 Conduit box kit, MKME-CBA0, MKME-CBA, MKME-CBB, MKME-CBC, MKME-CBD.

Communication cards: EMM-SAF01

Back Plate Kit: MKM-EPA, MKM-EPB, MKM-EPC, MKM-EPD.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations>.

